



**Explosion protected diesel engines  
Internal combustion engines  
powering plant used in areas of  
underground coal mines classified as  
explosion risk zone 1**

Coal Mining Safety and Health Act 1999  
Recognised Standard – 03

This document is issued in accordance with *PART 5—RECOGNISED STANDARDS* of the *Coal Mining Safety and Health Act 199* (the Act).

**“PART 5—RECOGNISED STANDARDS**

*Purpose of recognised standards*

71. *A standard may be made for safety and health (a “recognised standard”) stating ways to achieve an acceptable level of risk to persons arising out of coal mining operations.*

*Recognised standards*

- 72.(1) *The Minister may make recognised standards.*
- (2) *The Minister must notify the making of a recognised standard by gazette notice.*
- (3) *The chief executive must keep a copy of each recognised standard and any document applied, adopted or incorporated by the recognised standard available for inspection, without charge, during normal business hours at each department office dealing with safety and health.*
- (4) *The chief executive, on payment by a person of a reasonable fee decided by the chief executive, must give a copy of a recognised standard to the person.*

*Use of recognised standards in proceedings*

73. *A recognised standard is admissible in evidence in a proceeding if—*
- (a) *the proceeding relates to a contravention of a safety and health obligation imposed on a person under part 3; and*
  - (b) *it is claimed that the person contravened the obligation by failing to achieve an acceptable level of risk; and*
  - (c) *the recognised standard is about achieving an acceptable level of risk.*

Also relevant to the application of a Recognised Standard is Section 37(3) of the Act.

- 37.(3) *Subject to subsections (1) and (2), if a recognised standard states a way or ways of achieving an acceptable level of risk, a person discharges the person’s safety and health obligation in relation to the risk only by—*
- (a) *adopting and following a stated way; or*
  - (b) *adopting and following another way that achieves a level of risk that is equal to or better than the acceptable level.”*

Where a part of a Recognised Standard or other normative document referred to therein conflicts with the Coal Mining Safety and Health Act 1999 or the Coal Mining Safety and Health Regulation 2001, the Act or Regulation take precedence.

**This recognised standard is issued under the authority of the Minister for Natural Resources and the Minister for Mines**

*[Gazetted 12 December 03]*

ISBN .....

Note: This document is controlled electronically. To ensure that this copy is current either contact the Department of Natural Resources and Mines Website at [www.nrm.qld.gov.au](http://www.nrm.qld.gov.au) or the nearest office of the Department of Natural Resources and Mines.

Version No	Date
1	12 December 2003

**RECOGNISED STANDARD 03  
EXPLOSION PROTECTED DIESELENGINES  
INTERNAL COMBUSTION ENGINES POWERING PLANT USED IN  
AREAS OF UNDERGROUND COAL MINES CLASSIFIED AS  
EXPLOSION RISK ZONE 1**

**CONTENTS**

<b>1. PURPOSE.....</b>	<b>4</b>
<b>2. SCOPE.....</b>	<b>4</b>
<b>3. APPLICATION FRAMEWORK.....</b>	<b>4</b>
<b>4. CONTROLS AND TESTING .....</b>	<b>5</b>
<b>5. DEFINITIONS.....</b>	<b>5</b>
<b>6. REFERENCES –NORMATIVE.....</b>	<b>6</b>
<b>7. INFORMATIVE STANDARDS.....</b>	<b>6</b>

# RECOGNISED STANDARD No 03

## EXPLOSION PROTECTED DIESEL ENGINES INTERNAL COMBUSTION ENGINES POWERING PLANT USED IN AREAS OF UNDERGROUND COAL MINES CLASSIFIED AS EXPLOSION RISK ZONE 1

### 1 PURPOSE

To assist manufacturers and users of plant powered by internal combustion engines to meet the requirements of section 261(2) of the Coal Mining Safety and Health Regulation 2001(CMSHR2001): section 261(2) addresses the requirements of internal combustion engines used to power plant operated in an Explosion Risk Zone 1 (ERZ1) in an underground coal mine.

*s261(2) The underground mine manager must ensure an internal combustion engine used to power plant in an ERZ1 is -*

- (a) a compression ignition type; and*
- (b) a type that has been tested by a nationally accredited testing station under A/NZS 3584.2:2003 “Diesel engines systems for underground coal mine –explosion protected; and*
- (c) assessed by the engine’s manufacturer, having regard to the recognised standard for explosion protected diesel engine systems, as safe to use in an ERZ1; and*
- (d) clearly marked with information identifying -
  - (i) the test report for the test mentioned in paragraph (b); and*
  - (ii) the assessment report for the assessment mentioned in paragraph (c)**

*(3) The underground manager must ensure an internal combustion engine is not used to power plant in an ERZ0.*

*(4) In this section-*

*“AS/NZS” means a joint Standards Australia and Standards New Zealand standard*

### 2 SCOPE

This standards applies to internal combustion engines powering plant in an ERZ1 of underground coal mines in Queensland.

### 3 APPLICATION FRAMEWORK

Internal combustion engines used to power plant used underground in coal mines in Queensland must be of the compression ignition type refer *section 261 Using plant powered by internal combustion engines* (CMSHR2001). When diesel engines are used in underground mines they introduce safety and health hazards and must be designed and built (and maintained) to ensure that the risks associated with these hazards are properly managed.

The major safety hazards associated with using diesel engines underground in a coal mine are explosion and fire. Explosion is the result of the engine igniting an explosive mixture of gas usually methane which is naturally present in most underground coal mines; fire caused by diesel engines is usually the result of igniting spilt fuel or coal dust on hot surfaces.

Areas of an underground coal mine are given a risk zone rating depending on the probability of there being an explosive mixture of gas in that particular area. In order of descending probability of there being a presence of an explosive mixture of gas areas are zoned ERZ0, ERZ1 and NERZ.

ERZ0 is the area of a mine in which there is an unacceptably high probability that there will be a presence of methane in a concentration greater than 2% and it is considered that there is an unacceptable level of risk for an internal combustion engine to operate in an area with this classification.

ERZ1 is an area of a mine in which on almost all occasions the methane level will vary between 2% and 0.5% but there is the possibility on some occasions the concentration will exceed 2% creating an unacceptable level of risk of an explosion on the occasions such an event occurs; refer section 288 of CMSHR2001 for full definition of ERZ1 zone. Diesel engines used in these zones need to be explosion protected.

NERZ is an area of the mine where it is considered there is negligible risk of an explosive mixture of explosive gas being present.

This standard addresses the testing and assessment of engines to ensure that they are explosion protected and can operate safely in areas of the mine classified as ERZ1.

### **NOTE: RECOGNISED STANDARDS ARE NOT MANDATORY**

*Recognised Standards are not mandatory; but when followed provide a way of meeting safety and health obligations. A person may adopt another way of managing that risk, however, in the event of an incident the person may be required to show that the method adopted was equivalent to the method in the recognised standard.*

#### **4 CONTROLS AND TESTING**

The controls and testing contained in this recognised standard are:

1. those provided in Australian and New Zealand Standard AS 3584:2 2003, Australian/New Zealand Standard, Diesel engine systems for underground coal mines, Explosion protected"; and.
2. the requirement that where non metallic filter material is tested in accordance with Appendix H of AS/NZ 3584:2:2003 and the material is treated with a water soluble flame retardant material the test on the clean filter shall be carried out after the washing the material to remove the water soluble retardant.

#### **5 DEFINITIONS**

**Risk assessment** – An assessment of the risks associated with an activity and it should be in accordance with AS/NZ 4360: 1999 Risk management.

**Normative** – Refers to a standard or document that forms an integral part of the recognised standard in which it is mentioned.

**Informative** – Refers to a standard or document that is only for information and guidance.

## **6 REFERENCES**

### **NORMATIVE STANDARDS**

The following documents are referred to, directly or indirectly, in this standard:

**AS/NZS 4360: 1999 – Risk management**

**AS/NZS 3584:2; 2003 Diesel engine systems for underground coal mines ; Explosion protected**